



Optional Auxiliary Connection Block For PT100 and/or Water Detector

| POWER | Stack Length<br>L <sub>1</sub> | L    | L2   | L3   | Weight no Oil |
|-------|--------------------------------|------|------|------|---------------|
| 50HP  | 140                            | 486  | 435  | 385  | 14.0          |
| 75HP  | 180                            | 526  | 475  | 425  | 16.0          |
| 100HP | 240                            | 586  | 535  | 485  | 19.9          |
| 125HP | 300                            | 646  | 595  | 545  | 22.4          |
| 150HP | 360                            | 706  | 655  | 605  | 25.5          |
| 200HP | 480                            | 826  | 775  | 725  | 31.6          |
| 250HP | 600                            | 946  | 895  | 845  | 37.7          |
| 335HP | 800                            | 1146 | 1095 | 1045 | 47.6          |

Drive Arrangement to be modified to suit Hyd Pump

|                                      |            |             |            |                          |                        |        |       |
|--------------------------------------|------------|-------------|------------|--------------------------|------------------------|--------|-------|
| TYPE                                 | R0V144     |             |            | NAME                     | Standard Cross Section |        |       |
| NO.                                  | 1-010-0339 |             |            | REVISION                 | B                      | WEIGHT | SCALE |
| DESIGN BY                            |            | APPROVED BY |            | MATERIAL                 |                        |        |       |
| CHECKED BY                           |            | DATE        | 19/05/2009 | Aluminium-Black Anodised |                        |        |       |
| <b>SUBMERSIBLE MOTOR ENGINEERING</b> |            |             |            |                          |                        |        |       |